



27" Self-service Kiosk - Floorstand

The self service kiosk touch screen is an innovative solution that has transformed the food retail industry, providing customers with a convenient self ordering system, QR code scanner, and 24/7 availability. We understand that this technology can greatly benefit your business.



Highlights



QR Code Scanner & Thermal

features an LED light to improve reading ability and can be used to scan barcodes or QR codes in conjunction with special offers or to place orders.



Easy Maintenance & Cleaning optional Cloud Update

Tool-free maintenance is possible via the lockable front access door, allowing store staff to swap out and replace components without removing from the wall. Touch screen & barcode scanner are recessed into enclosure to wipe clean surface.



24/7 Commercial Use

As many quick service restaurants and supermarkets are open 24/7 any kiosk solution needs to be up to the task of being in continuous use.



Anti-theft Mounting Options

The kiosk can be securely mounted directly to the wall from inside the lockable door providing an anti-theft flush fit. There is also an optional floor stand available on request when wall mounting is not possible



Durable Protective Glass

The glass front is thermally toughened but also has a special anti-scratch 6H hardness coating. There is also a special coating on the panel which reduces annoying reflections created by external light sources.



Integrated Receipt Printer

Integrated receipt printer saves space, speeds up service, and boosts sales by combining dynamic promotions with seamless transaction printing in one sleek device.



Specifications

General

Model	YJC-270-K
Screen Size	27"
Screen Active Area(mm)	597.9×336.3
Resolution	FHD(1920×1080)
Aspect Ratio	16:9
Brightness(nits)	300 nits
Contrast Ratio	1200:1
Viewing Angle(H/V)	178°/178°
Backlight Life Cycle	50,000 Hrs
Operation Hours	24/7
Response Time	6ms
Screen Orientation	Portrait

System

OS	Android 11
CPU	RK3568, Quad-core 2.0GHz
GPU	The Mali-G52 GPU supports OpenGL ES 1.1/2.0/3.2, OpenCL 2.0, and Vulkan 1.1.
DDR	DDR 2GB
ROM	32GB EMMC
Language	English/Multilingual

Connectivity

Input	USB x2, Ethernet RJ45 x1
-------	--------------------------

Network connection

Wifi or LAN	Yes
3G/4G connection	Optional

Speaker

Build in speaker	Yes
BT Speaker Support	Yes

Power

Power Supply	AC 100~240V,50/60Hz
Power Type	Built-In Power
Power Consumption	35W(Max.)

Physical

IP rating	IP5X
Glass	Yes
Shell	Cold-rolled steel sheet
Standard Color	Black + White
Dimensions	1800(H)×462(W)×190(D) mm
Net Weight	27 kg
Packing Dimensions(W×H×D)	1150 x 540 x 260 mm 890 x 230 x 400 mm
Installation Method	Floorstand

Operations

Working environment	Indoor
Operation Temperature	0°C to 45°C
Operation Humidity	10% to 80%
Storage Temperature	-10°C to 50°C
Storage Humidity	10% to 80%

What's in the box

Accessories	Power cable x 1
	Screw package x 1
	POS bracket x 1
	Antenna
	User Manual (Electronic Version)

Dimensions

